


## MSA Compatible CWDM SFP Modules

1000Base-LX/Fiber Channel 1x Single Mode (LC) With DMI



TN-SFP-LX16-C55

Applications include: Gigabit Ethernet Switches and Routers, Fiber Channel Switch Infrastructure, xDSL Applications, and Metro Edge Switching.

### Features

- Coarse Wavelength Division Multiplexing (CWDM) ITU Grid Compliant Wavelengths
- Hot-Pluggable SFP Footprint Duplex LC Optical Transceiver
- Digital Diagnostic Function (DMI)
- Compliant with SFP Multi-Sourcing Agreement (MSA)
- Compliant with 1000Base-ZX
- Compliant with Fiber Channel 1X SM-LC-L FC-PI (Can be used on Optical Line Converter xFMFF4040-100)

### Specifications

Standards	IEEE 802.3 2003 IEEE 802.3z ANSI X3.297-1997
Output Wavelength	-5.5nm < $\lambda_c$ < +7.5nm
Dimensions	Width: 0.52" [13 mm] Depth: 2.18" [55 mm] Height: 0.33" [8 mm]
Power Consumption	0.66 Watts
Power Input	3.3V
Environment	Operating: 0°C to 70°C
Certifications	IEC-60825, FDA 21, CFR 1040.10 and 1040.11
Warranty	Lifetime

Transition Networks' SFP units fully comply with Multi-Sourcing Agreement (MSA). This compliance allows Transition Networks' SFP modules to be used on other MSA-compliant SFP platforms without any problems.

### Ordering Information

Duplex

#### TN-SFP-LX16-Cxx

1000Base-LX/Fiber Channel 1x single mode (LC) with DMI [160 km/99.4 mi.] Link Budget: 37.0 dB

xx = center wavelength (l)

31 = 1310nm	51 = 1510nm
33 = 1330nm	53 = 1530nm
35 = 1350nm	55 = 1550nm
39 = 1390nm	61 = 1610nm
47 = 1470nm	